



SIDEWINDER

SPECIFICATIONS / TECHNICAL DATA REV A

KEY FEATURES

- 50,000 cu.ft/min
- (4) 8-Second 20' Bursts
- 180° Multi Position Fog Burst
- (22) 3w RGBA Leds
- Durable Tour-Ready Aluminum Housing

SPECIFICATIONS

Dynamic Effects

- . 54 Built-In Programs
- . Patented Instant Stop Function
- . (22) 3w Leds (5 Red, 6 Green, 6 Blue, 5 Amber)
- . Max Continuous Output: 8 Seconds

Control

- . DMX512 Protocol
- . DMX Modes: 3
- . DMX Channels: 1, 4, 7
- . RDM (Remote Device Management)
- . Touch Screen Display
- . On-Board Timing Control
- . Stand Alone Mode
- . 4-pin Wired Remote
- . Manual Fogging

Connections

- . Data Connectors: 5-pin XLR In/Out, 4-pin XLR Out
- . Locking Power Connector

Construction / Physical / Performance

- . Dimensions (LxWxH): 14.80 x 7.60 x 16.26 in. / 376 x 193 x 413 mm
- . Weight: 31.06 lbs / 14.08kg
- . Fluid Consumption: 180ml/min.
- . First Warm Up Time: 540s (9 minutes)
- . Cyclic Heating Up Time: 60s (1 minute)
- . Max Continuous Output Duration: 8 Seconds
- . Fluid Tank Capacity: 2.5L





SIDEWINDER

SPECIFICATIONS / TECHNICAL DATA REV A

Electrical

- . Input Voltage: 120V, 230V, 240V, 50/60Hz
- . Heater Power: 1450w
- . Power Consumption: 1560w
- . Breaker Size: 20A (120V Version)
- . Breaker Size: 10A (230/240V Version)

Certifications / Qualifications / Thermal

- . Cooling: Fan Cooled
- . Maximum Temperature (Ambient): 104° F (40° C)
- . Exterior Surface Temperature: 140° F (60° C)
- . CE | cETLus (pending) | IP20

What's Included

- . 14 AWG Locking Power Cable
- . (2) Omega Brackets

Optional Accessories

- . MAGFLY Card
- . MAGAPP Card
- . MAG-RF Card
- . Recommended Fluid: Atmosity Flash Fog Fluid (AFF-2L, AFF-4L & AFF-20L)



413 mm
(16.26 in.)



193 mm
(7.60 in.)

376 mm
(14.80 in.)

MAGMATIC