

## grandMA3 processing unit L

Art.-No. 4010509



Expanding the grandMA3 system is simple with addition of grandMA3 processing units! The grandMA3 processing unit L expands the system by 8 192 parameters and offers frame-synchronous calculation of the parameters within the MA-Net3 environment. Designed for larger systems, the L model offers a more cost effective and compact solution for parameter expansion. Additionally, the grandMA3 processing unit L offers a Mode2 to expand existing grandMA2 systems by 4 096 parameters.

The grandMA3 processing units are designed for rack mounting and all models are only 2RU, allowing for efficient touring solutions. Each model is equipped with 8 DMX outputs for frame-synchronous DMX output throughout the network. Additional frame-synchronous DMX outputs are available with the addition of grandMA3 xPort Nodes.

grandMA3 processing units offer a perfect system overview on the integrated touchscreen. This easy access to important functions allows for best maintenance if installed in a dedicated rack whilst every function can be monitored from the grandMA3 session.

For larger systems it is suggested to keep the grandMA3 processing units in a centralized position for parameter expansion and to use grandMA3 xPort Nodes to distribute and output the frame-synchronous DMX data.

Scope of delivery

ArtNo.	Article	Quantity
4025593	MA Quick Manual for grandMA3 processing units	1

1x powerCON TRUE1 socket (NAC3FX-W-TOP)



## Technical Specifications

Parameters	8 192 (HTP/LTP)
Parameters Mode2	4 096 (HTP/LTP)
Operating voltage/ Supply	AC 100 - 240 V; 50/60 Hz
voltage	
Power	max. 200 VA
Operating Temperature	0 °C up to 40 °C / 32 °F up to 104 °F
Dimensions	482 x 372 x 87 mm / 19 x 15 x 4 in
	(width x depth x height)
Net weight	5 kg / 12 lbs
Connectors	1 x powerCON TRUE1
	2 x etherCON/RJ45
	8 x DMX512-A Out (5pin XLR female)
	3 x USB 2.0 (type A)

## Article

ArtNo.	Article
4010509	grandMA3 processing unit L

## More product pictures



