

# RIGGING PRODUCTS

## ELLERSLING ROUND SLINGS

Ellersling polyester round slings are used when materials like chain or wire rope could damage the load.

### MAIN FEATURES:

- According to standard EN 1492-2;
- Safety factor 7;
- Label in protective cover;
- Computerized stitching;
- Double woven jacket;
- Polyester;
- Sealed per piece with CE declaration and manual.

### OPTIONAL FEATURES:

- Other capacities and lengths available on request.
- Printing on label of company logo / name on request possible.



ARTICLE CODE	WLL (t)	CIRCUMFERENCE (m)	EFFECTIVE WORKING LENGTH (m)	QUANTITY
ESER01-02Z	1	2	1,0	50
ESER01-03Z	1	3	1,5	45
ESER01-04Z	1	4	2,0	35
ESER01-06Z	1	6	3,0	20
ESER02-02Z	2	2	1,0	45
ESER02-03Z	2	3	1,5	35
ESER02-04Z	2	4	2,0	20
ESER02-06Z	2	6	3,0	15



Label with barcode

Colour	Safe Working Load				
	1	0,8	2	1,4	1
	Straight lift	Choked lift	Parallel	$\alpha = \text{up to } 45^\circ$	$\alpha = 45^\circ \text{ up to } 60^\circ$
WLL (t)					
1	1	0,8	2	1,4	1
2	2	1,6	4	2,8	2